





Mayer & Cie. GmbH & Co. KG
Tailfingen · Emil-Mayer-Straße 10 · D - 72461 Albstadt
Postal address: Postfach 20 15 80 · D - 72438 Albstadt
Tel. + 49 (0)7432 7000 · Fax + 49 (0)7432 700315
E-mail: sales@mayercie.de · www.mayercie.com

"The world champion in the fine gauge single jersey jacquard machine sector".

For single jersey jacquard with fully electronic needle selection.

With gauge E 60 this machine breaks all hitherto existing limits in the production of circular knitting single jersey fabrics.

The unlimited pattern variety which is now also possible for extremely fine fabrics opens up completely new collection possibilities particularly to manufacturers of night and underwear.


But also manufacturers of technical applications are likely to become interested in the new fabric qualities.

MJ 3.2 E DNS



Advantages of MJ 3.2 E DNS

- The first ultra fine gauge electronic jacquard machine all over the world
- Needle selection with a million times proved Mayer mono magnet system
- Automatic temperature controlled
- 2-way-technique for highest productivity
- 3-way-technique for unlimited design
- A new dimension of fabrics for Shapewear products
- Super fine gauge Jacquard for noblest surface look




STANDARD		OPTION	
		***************************************	Flexcreel without tubes Flexcreel with alu-tubes Flexcreel-circular creel with alu-tubes air-jet for Flexcreel
			elastomeric plating jacquard feeding units
I LE	 1 type of cylinder needles 1 type of control sinker 2 control magnets/feeder 1 type holding-down sinkers 		
	1 needle track 3-way-technique by 2 systems positive needle guidance, independent of stitch length adjustment		2-way-technique with 96 feeders (includes yarn guide and cam parts) + stitch cams
	portal frame for 520 mm fabric rolls		industrial frame for 920 mm fabric rolls open-width frames steps for the open-width frame sliding platform industrial open-width frame
②	frequency controlled drive (AC) 400 V, 50/60 Hz, 4 KW 4 KW peripheral units machine controller with colour display, touch screen and USB-port control voltage 24 V	4	200 - 260 volt 346 - 600 volt fabric light in the side legs add. light assembled in the yarn feeding
	adjustable take down with positive drive rubber covered rollers MCT trapezoid spreader		fabric work box folding device MCT trapezoid spreader rollers and take down rollers for elast. and sensitive yarn fabric cutting device 3 - roller take down MFT - multi function take-down
© © © ©	SENSO P pressure oiler (oil: VG 22, VI 110±20) 5-shift counter central control for oiler, counter and peripheral accessories working hour counter stationary and rotating lintblower (air: min 6 bar, 250 l/min) peripheral equipment control by display VK 3		• VG 3
	needle detectors electr. supervision system with display (e.g. yarn feeding systems, oiler, safety, guards and pneumatic unit) datatransfer via Bluetooth		MDS 1 (Mayer Design Software) rapport and striper-software battery in case of power failure Interface for MDA gauge/magnet fixing













(stick to be provided by customer)